



Good people. Great products.

PRODUCT LINE



FOR THE BUS & MOTOR COACH INDUSTRY

ENGINE OILS

#700 SUPREME 7000™ SYNTHETIC PLUS 15W40

#711 SUPREME 7000™ SYNTHETIC PLUS 10W30

Para-Synthetic, Multi-grade Engine Oil, CJ-4/CI-4/CI-4 Plus/SM, 10-TBN, 1.0% Sulfated Ash, MACK EO-O Premium Plus-07, Detroit Diesel, Powerguard, 93K218, CAT ECF-1--a, ECF-2, ECF-3; Cummins, CES 20081, Volvo VDS-4, ACEA E7-10 & E9-10.

#701, #702, #703, #704 SYNTHETIC PLUS

5W-30, 10W-30, 5W20, SAE 30 AND 40, Para Synthetic Engine Oil, SN, ILSAC GF-5.

#9000 SUPREME 9000™ FULL SYNTHETIC ENGINE OIL SAE 5W-40

CJ-4/CI-4/CI-4 Plus/SM, 10-TBN, 1.0% Sulfated Ash, MACK EO-O Premium Plus-07, Detroit Diesel Powerguard, I 93K218, CAT ECF-1-a/ECF-2/ECF-3, Cummins CES 20081, Volvo VDS-4, ACEA E7-10 & E9-10 Volkswagen 505.01.

#9003D SUPREME 9000™ FULL SYNTHETIC ENGINE OIL SAE 5W30

SN, ILSAC GF-5. Meets GM dexos1™.

#114S SYN. PLUS NAT. GAS ENGINE OIL

SAE 30 and 40, Para-Synthetic, 0.45% ash content. Protects natural gas engines without leaving deposits.

#114CNG SYN. PLUS NAT. GAS ENGINE OIL

15W40, Para-Synthetic, 0.6% ash content. For CNG, LNG, LPG powered vehicles. API CF Cummins, CES 200074, Detroit Diesel 93K216, Mack CNC, Volvo CNG, John Deere CNG/LNG.

TRANSMISSION FLUID

#204SAT ALL-TRANS SUPREME®

Full Synthetic Multi-vehicle, Dexron III-H / Mercon® / Mercon®. Also Exceeds Allison, TES295 & TES389, Chrysler ATF, JASO A-1 Specs.

#205 DEXRON® VI

Full Synthetic ATF. Meets GM Dexron® VI

#113 VARNICLEAN®

Removes varnish buildup and sludge. Significantly reduces equipment downtime. Cleans equipment while operating.

FUEL ADDITIVES

#137ND DIESEL TREAT 2000™ ULTRA LOW SULFUR

(Summer Treat) 1 gal. treats 2,000 gal. Cetane improver. Contains fuel economy package. Year-round fuel additive for jobbers and fleets. Cummins L-10 Superior Performance. Upgrades #2 to Premium. Contains SynShield®. Contains <15 ppm of sulfur.

#137 DIESEL TREAT 2000™ ULTRA LOW SULFUR

Same as #137ND in pints. One pint treats 125 gal. fuel.

#137 USLW DIESEL TREAT 2000™ ULTRA LOW SULFUR

WINTER PREMIUM, 1 gal. to 1,000 gal. fuel. Flow improver / fuel economy package. Cummins L-10 Superior Performance. Contains SynShield®/Cold Weather storability and <15 ppm of sulfur.

#300 ULSW ARCTIC SHIELD™ + ULTRA LOW SULFUR

(Winter Treat) 1 gal. to 1,500 gal. fuel for economy level of protection. Anti-gel and jet fuel deicer with EXTRA anti-ice and EXTRA anti-gel protection. Contains <15 ppm of sulfur.

#141 BIOTREAT™ PREMIUM DIESEL

1 gal. to 1,500 gal. diesel fuel. Upgrades B2-B20 blends to Premium Diesel. Increased oxidation stability, controls moisture.

#137CT CARBON TREAT

1 gal. to 1,500 gal. diesel fuel. Prevents formation of black sludge. Prevents filter plugging caused by thermal stressing within the engine. Restores lost horsepower. Cleans and prevents deposits formed in high-pressure fuel injection systems. Also available in WINTER, EXTRA CETANE AND SUMMER formulations.

#139A SOYSHIELD® ALL SEASON

1 gal. to 500 gal. Cetane improver, Contains fuel economy pkg. Cummins L-10 Superior Performance. Upgrades #2 to Premium. Improves lubricity with Soy Oil, Cold Flow Improver. Contains <15 ppm sulfur.

#284 DIESEL HOT LINE EMERGENCY TREATMENT

An Emergency Treatment that immediately dissolves ice and wax forming in gelled diesel fuel. Contains <15 ppm sulfur.

GEAR LUBES

#2937590 SUPREME GEAR LUBE SYN. PLUS

75W90, Para-Synthetic, w/Soluble Moly, w/o tackifier. EP, GL-5, MT-1, MIL-PRF-2105E, SAE J2360.

#293A SUPREME GEAR LUBE NO TACK

80W90, ISO 150 AND 220, Para-Synthetic, w/Soluble Moly, E.P., GL-5, MT-1, MIL-PRF-2105-E, J2360 US Steel 224, AGMA 9005-E02 Pour Point -15°F to -20°F.

#239S SUPER LUBE SUPREME

SAE 10, 30 & 50. Contains soluble moly. Cat TO-4, Para-synthetic Cat Powershift Transmissions Hydraulics & Cat Final Drives Eaton Road Ranger & Spicer Meritor Transmissions (SAE 50 only), Allison C-4, Komatsu Kes 07.8C2 and 07.868.1.

#214S SUPREME ONE FOR ALL 80W-140

Para-Synthetic, Multi-grade Gear Lube, E.P., GL-5, MIL-PRF-2105-E, SAE J2360, Pour Point -25°F.

#751M SYNTHETIC LUBE E.P. 75W90 W/M

Full Synthetic, E.P. Gear Lube, Contains Soluble Moly. Meets GL-5, MT-1, MIL-PRF-2105-E & SAE J2360. Eaton Road Ranger, Dana, Meritor. Meets Ford spec for full synthetic 75W90.

#167 PURE SYNTHETIC GEAR LUBE 75W140

Full Synthetic. ISO 150, 220, 320, 460, 680 & 1000. E.P., GL-5, MIL-PRF-2105-E, SAE J2360, US Steel 224, AGMA 9005-E02

#740 SYNTHETIC LUBE E.P. 80W140 E/A

#741 SYNTHETIC LUBE E.P. 75W90 E/A

Full Synthetic, Meets GL-5, MT-1, MIL-PRF-2105-E & SAE J2360. Eaton Extended Warranty Approved, Road Ranger, Meritor (Rockwell) Approved.

#742 SYNTHETIC LUBE 50 E/A

Full Synthetic, Eaton Extended Warranty Approved, Meets Eaton PS-664 (Rev 7) Meritor (Rockwell) Approved.

FOR MORE INFORMATION PLEASE CONTACT:

Dan the Oil Man

Independent Consultant

(573) 578-2801

dhalinar@fidnet.com

schaefferoilreps.com/dantheoilman

GREASE

#238 ULTRA SUPREME

NLGI #1, #2 and #3, Para-Synthetic, Extreme Pressure Grease. Contains extra MoS2 / other solids. Aluminum Complex Base. Meets Cat's 5% Moly Spec. Extra Tacky / Waterproof / Hi-Temp.

#274 MOLY E.P. SYNTHETIC PLUS GREASE

NLGI #00, #0, #1 and #2, Para-Synthetic, Extreme Pressure Grease, Aluminum complex base, water proof, Low temperature / pumpable to -35°F.

#274M2 MOLY E.P. SYNTHETIC PLUS GREASE

Same as 274; Meets Cat's 5% moly specification.

#229 ULTRA RED SUPREME GREASE

Para-synthetic, Extreme Pressure Grease, Aluminum Complex Base, Extra Tacky, Contains synthesized moly. Red color. Water proof/Hi-Temp.

#200 SILVER STREAK® (Aerosol)

#200S SILVER STREAK® SPECIAL

Para-Synthetic multi-service fifth-wheel lube. Contains lubricating solids. Does not contain any solvents. TCLP Safe.

SPECIALTY PRODUCTS

#132 MOLY E.P. OIL TREATMENT

1 pt. treats 5 qts. oil. Contains Micron Moly® and Penetro®. Reduces friction and oil consumption.

#258 CLEAN & COOL RADIATOR TREATMENT

1 pt. treats an 8 gal. cooling system, Corrosion inhibitor/radiator treatment. Reduces electrolysis/cleans up scale. Not recommended for recommended for use in extended life coolants.

#266 CITROL® DEGREASER

Biodegradable, heavy-duty, citrus-based degreaser. Dilutes with water up to 15:1. Aerosol.

#190 PENETRO 90® PENETRATING OIL

Lubricating & penetrating oil. Designed to unfreeze, lubricate and protect practically anything. Aerosol.

#743 SCHAEFFERSEAL™ TIRE SEALANT

Seals punctures of 3/8" inch in any air filled tire. Can be used in high speed, low speed, tubeless or tube type. Water soluble.

#928 WEBSCOPE PMSM WITH TBN

Web based oil analysis eliminates cost of handling "paper based" reports. Return mail time is eliminated. Log on to Schaeffer's internet site to view reports. Hard copy may be printed if desired. Six individual kits per case.